



Technical Bulletin and Application Guideline

Page: 1 of 1
November 2003

BOMANITE INTERIOR FLOOR STRIP **HEAVY DUTY STRIPPER CONCENTRATE** **FOR WATER-BASE SEALS AND FINISHES**

PRODUCT DESCRIPTION

Bomanite Interior Floor Strip is a concentrated stripper and is not intended as a general purpose cleaner. The balanced formula is designed for fast, complete removal of polymer floor finishes and seals, such as Bomanite Interior Floor Finish, with low foaming and easy rinsing. When used according to directions, Bomanite Interior Floor Finish is safe to use on imprinted and/or colored concrete, composition tile, terrazzo, and similar floor surfaces. Do not use on cork or wood. If in doubt, consult your supplier or pre-test in an inconspicuous area.

APPLICATION

Dilute with six to 10 parts water for removal of Bomanite Interior Floor Finish. Allow solution to dissolve and raise old seal for five to 10 minutes before scrubbing. Let Bomanite Interior Floor Strip do the work for you. After scrubbing and pick up, rinse the floor and allow to dry. Bomanite Interior Floor Strip's efficiency allows for much faster and complete stripping without the need for harshly abrasive stripping pads or brushes. In many cases, light or medium scrub pads or brushes may be used.

SPECIFICATIONS

COLOR	Clear; yellow
ODOR	Citrus
COVERAGE (approximate).....	1000 square feet per gallon
SURFACE TENSION	29 dynes per cm.
pH	13.8 + 0.2 (concentrate) 12.9 + 0.2 (1:10 dilution)
FLASH POINT	None (C.O.C. Method)
DILUTION USE RANGE	1:6 to 1:10
DETERGENT TYPE.....	Nonionic
SPECIFIC GRAVITY.....	1.03
DENSITY	8.6 pounds per gallon
SOLUBILITY IN WATER.....	100% (hard, soft and/or deionized water)
SHELF LIFE	Minimum 1 year from date of sale
FREEZE/THAW STABILITY	Minimum 3 cycles (A.S.T.M. Test D-3209-82)
PACKAGE SIZES	4 x 1 gallon plastic jugs 5-gallon plastic pails 55-gallon plastic drums

SPECIFICATION ASSISTANCE

Consult Bomanite Corporation for specification assistance, detailing, etc. This consultation is highly recommended prior to specification.

WARRANTY

This product is warranted to meet uniform quality standards within conventional manufacturing tolerances. Since no control is exercised over product use, no warranty or guarantee, expressed or implied, can be made to its use. Seller's and manufacturer's obligation under this warranty is limited to reimbursement of the purchase price of the portion of the product proven to be defective. The user assumes all risks and liability resulting from the use of this product.