



Your Single Source For Innovative
Architectural Concrete Solutions

BOMANITE ALLOY

Technical Bulletin

Bomanite Alloy is an architectural exposed concrete with varying exposure depths using non-native quartz and decorative aggregates that are surface seeded on concrete. The Bomanite Alloy System utilizes specialized concrete mix designs, dry shake decorative aggregate hardener and/or integral color, topical treatments and advanced application procedures to produce a finished product that showcases the seeded aggregate.

The final product is unique alternate to other decorative concrete finishes while producing a monolithic concrete slab with a low life cycle cost due to the pre-aged nature of the surface. Bomanite Alloy is suited for exterior applications—anywhere that improved wear resistance for light- to moderate-duty vehicular or foot traffic combined with an architectural finish is necessary. Due to the use of Bomanite Color Hardener, these highly durable surfaces are available in a multitude of standard and custom options, including cost effective light-reflective formulations that may not require the use of white cement to reduce heat island effect.

Bomanite Alloy is intended for both new construction and major renovation projects. Bomanite Alloy is most commonly installed as full depth slab on grade pours along with un-bonded thick section toppings 3” or greater in thickness over membrane applications. The specialized design of the dry shake hardener along with placing and finishing are critical to the success of the finished product.

Typically applied products such as Bomanite Chemical Stain are compatible with Bomanite Alloy Systems. Consult the applicable technical bulletins for further information on these products and systems. Consult the Bomanite Sandscape Texture and Bomanite Revealed System Guidelines for additional exposed aggregate options.

FEATURES AND BENEFITS:

- *Decorative aggregate exposure*
- *Durable for sustainable design*
- *Highly architectural installations*
- *Increased surface slip resistance*
- *Permanent, lightfast coloration*
- *Wide range of aggregate options*

GENERAL INFORMATION:

Colors

Consult the Bomanite Coloration Systems Color chart for the full range of standard colors. Note that blues and greens may be marginally more expensive due to pigment types. Incorporating large aggregates into the concrete may dictate the use of Bomanite Integral Color in conjunction with Bomanite Color Hardener which will have an effect on the finished cost.

Maintenance

Consult the Bomanite Exposed Aggregate Systems Maintenance Guideline for complete information on how to maintain exposed aggregate paving.

Limitations

- Final color will be influenced by factors such as environmental variations etc. A thorough sampling and mock-up process is required as part of the installation of the system.
- Variation in aggregate exposure during the etching process is a factor with all surface seeded applications.
- Lack of protection from trade damage along with chemical exposure resulting in staining will detract from the quality of the finished product.
- Surface defects and repairs may be appreciably noticeable once the process is complete.

8777 Auburn Folsom Rd. #108, Granite Bay, CA 95746 • (303) 369-1115 • FAX: (303) 291-0282
Web site: www.bomanite.com • E-mail: info@bomanite.com • February 2013

Warranty

This product is warranted to be of uniform quality within manufacturing tolerances. Since control is not exercised over its use, no warranty, expressed or implied, is made as to the effects of such use. Seller and manufacturer obligations under this warranty shall be limited to refunding the purchase price of that portion of the material proven to be defective. The user assumes all other risks and liabilities resulting from use of this product.

Additional product information, technical bulletins and specifications are available online at www.bomanite.com or through one of our Bomanite Licensed Contractors. For additional assistance with specifications or technical issues, contact The Bomanite Company.