



Your Single Source For Innovative
Architectural Concrete Solutions

BOMANITE CEMENTITIOUS TOPPING

Cross Reference Guideline

Product Name	Resin Description	Powder Description	VOC Content Liquid	Recommended Uses	Unique Characteristics	Applied Thickness	SF per Coat per Bag	Hazardous Goods
Micro-Top	Proprietary	Portland cement with silica	< 30 grams per liter	<ul style="list-style-type: none"> Interior flooring product Exterior resurfacing with limited freeze-thaw exposure 	<ul style="list-style-type: none"> Interior concrete resurfacer with excellent troweling characteristics and color variety Designed as a wear surface if protected with an appropriate sealer or coating 	1/16" 2 base coats 2 finish coats	450 base coat 600-1000 finish coat	None
Micro-Top XT	Ethylene vinyl acetate	Portland cement with marble	< 5 grams per liter	<ul style="list-style-type: none"> Exterior resurfacing with extended freeze-thaw exposure 	<ul style="list-style-type: none"> Exterior resurfacer with superior flexibility and color variety Designed as a wear surface if protected with an appropriate sealer or coating Softer, more resilient than Micro-Top 	1/8" 2 base coats 2 finish coats	200 base coat 600-800 finish coat	None
Bomanite Thin-Set II	Ethylene vinyl acetate	Portland cement with silica	< 3 grams per liter	<ul style="list-style-type: none"> Interior flooring product Exterior resurfacing with moderate freeze-thaw exposure 	<ul style="list-style-type: none"> Interior or exterior concrete resurfacer with ease of use characteristics and color variety Designed as a wear surface if protected with an appropriate sealer or coating 	1/4" to 3/4" total one lift	22 @ 1/4" 16 @ 3/8" 11 @ 1/2"	None
Bomanite Repair Mortar	Styrene butadiene	Portland cement with silica	< 14 grams per liter	<ul style="list-style-type: none"> Interior below floor patching Exterior below resurfacing patching with moderate freeze-thaw exposure 	<ul style="list-style-type: none"> Interior or exterior patching product for pitching or general repairs Designed to be covered with an appropriate topping, sealer or coating Can be used over wood into 2.5 gauge lathe 	1/4" to 3/4" total one lift 1 1/2" with 20% rock	36 @ 1/4" 27 @ 3/8" 18 @ 1/2"	None

Product Name	Resin Description	Powder Description	VOC Content	Recommended Uses	Unique Characteristics	Applied Thickness	SF per Coat per Bag	Hazardous Goods
Bomanite Repair Mortar FA Fast Set	Carboxylated Styrene Butadiene	Sulfo-aluminate/ Portland cement blend with silica	0 grams per liter	<ul style="list-style-type: none"> Interior below flooring resurfacer Exterior below resurfacing patching with extended freeze-thaw exposure 	<ul style="list-style-type: none"> Interior or exterior fast-setting patching product for improved bond and moisture resistance or general repairs Designed to be covered with an appropriate topping, sealer or coating 	Tight to 1/4" total one lift	200 Tight 36 @ 1/8" 18 @ 1/4"	None
Bomanite Repair Mortar MP Regular Set	Carboxylated Styrene Butadiene	Portland cement with silica	0 grams per liter	<ul style="list-style-type: none"> Interior below flooring resurfacer Exterior below resurfacing patching with extended freeze-thaw exposure 	<ul style="list-style-type: none"> Interior or exterior standard-setting patching product for improved bond or general repairs Designed to be covered with an appropriate topping, sealer or coating 	Tight to 1/4" total one lift	200 Tight 36 @ 1/8" 18 @ 1/4"	None
Bomanite Flexible Repair Mortar	Acrylic	CA3/Portland cement with silica	< 30 grams per liter	<ul style="list-style-type: none"> Interior below flooring resurfacer for large areas or pitching from 1/4" Exterior below resurfacing patching with extended freeze-thaw exposure 	<ul style="list-style-type: none"> Interior or exterior medium-setting patching Designed to be covered with an appropriate topping, sealer or coating Excellent for pitching over wood into 2.5 gauge lathe 	1/4" to 3/4" total one lift	20 @ 1/4" 15 @ 3/8" 10 @ 1/2"	None
Bomanite Self Leveler	Proprietary	Portland cement with silica	N/A	<ul style="list-style-type: none"> Interior flooring product for resurfacing large areas 	<ul style="list-style-type: none"> Interior rapid setting flowable concrete resurfacer Designed as a wear surface if protected with an appropriate sealer or coating For use as a fast patch under Micro-Top 	1/4" to 3/4" total one lift	24 @ 1/4" 18 @ 3/8" 12 @ 1/2"	None
Bomanite SL-Underlayment	Proprietary	Portland cement with silica	N/A	<ul style="list-style-type: none"> Interior flooring product for resurfacing large areas or feather edging isolated areas 	<ul style="list-style-type: none"> Interior rapid-setting flowable concrete resurfacer Designed as a residential wear surface if protected with an appropriate sealer or coating For use as a fast patch under Bomanite Thin-Set II or other 1/4" product 	Tight to 3/4" total one lift	48 @ 1/8" 24 @ 1/4" 12 @ 1/2"	None