



Your Single Source For Innovative Architectural Concrete Solutions

# Technical Bulletin and Application Guideline

Page: 1 of 2  
June 2009

## BOMANITE CLEAR CURE CONCRETE CURING MEMBRANE & SEALER

### PRODUCT DESCRIPTION

Bomanite Clear Cure is a water-based membrane curing compound and sealer designed to increase the impact strength and protect new concrete, colored or natural. It is also excellent as a seal to dust-proof concrete and repel water and stains. It is suitable for both interior and exterior use, and will not yellow, haze or flake. Bomanite Clear Cure complies with VOC regulations for the state of California, including BAAQMD and SCAQMD (less than 250 g/l VOC content). Before use, consult state and local regulations or contact the United States Environmental Protection Agency (E.P.A.) to determine if this product complies with VOC regulations in your area.

### APPLICATIONS

#### *CURING NEW CONCRETE*

Bomanite Clear Cure is ready to use. Do not dilute. Apply after broom or trowel finishing, when surface moisture has completely disappeared. Apply with an airless sprayer, pump-up sprayer or short nap roller. Coat the surface uniformly, without leaving puddles or spaces. Coverage will vary, approximately 300-400 square feet per gallon for rough or broom finish, 400-600 square feet per gallon for smooth finish. For maximum hardness development and oil resistance, apply a second coat after first coat fully cures (approximately 12 hours). Let second coat cure for 12 hours before opening to traffic.

#### *SEALING EXISTING CONCRETE*

Surface must be thoroughly cleaned, rinsed and allowed to dry. Apply one or more coats using a sprayer, lambswool applicator or string mop. Coverage will vary, approximately 300-500 square feet per gallon for rough finish, 400-600 square feet per gallon for smooth finish. Do not allow Bomanite Clear Cure to puddle. Apply two thin coats rather than one heavy coat. Allow each coat to dry thoroughly before applying additional coats.

### SPECIFICATIONS

TYPE OF PRODUCT .....	Water base acrylic emulsion; contains no petroleum distillates, paraffins or waxes
BASE COLOR.....	Milk white, dries clear
ODOR .....	Slight, sweet
REFRACTOMETER SOLIDS.....	22.5%
APPLICATION METHOD .....	Spray, finish broom, lambswool applicator
APPLICATION RATE .....	300 to 600 square feet per gallon
AVERAGE MIL THICKNESS: .....	(Per coat) 2 mils on a sealed surface; on fresh concrete, variable from 1 to 2 mils depending on porosity of concrete and curing time.
MOISTURE VAPOR TRANSMISSION .....	Conforms to ASTM C-309 Specifications (at 300 square feet per gallon coverage)
WATER RETENTION .....	Conforms to ASTM C-156 Specifications (at 300 square feet per gallon coverage)
DRY TIME	
SET TO TOUCH .....	20 minutes
DRY HARD .....	1 hour
READY FOR TRAFFIC.....	12 hours
VOC CONTENT .....	Less than 250 grams per liter
FLASH POINT.....	None (C.O.C. method)
PACKAGE SIZES .....	1-gallon, 5-gallon, and 55-gallon containers



Your Single Source For Innovative  
Architectural Concrete Solutions

# Technical Bulletin and Application Guideline

BOMANITE CLEAR CURE

Page: 2 of 2

June 2009

## **SPECIFICATION ASSISTANCE**

Consult The Bomanite Company for specification assistance, detailing, etc. This consultation is highly recommended prior to specification.

## **WARRANTY**

This product is warranted to meet uniform quality standards within conventional manufacturing tolerances. Since no control is exercised over product use, no warranty or guarantee, expressed or implied, can be made to its use. Seller's and manufacturer's obligation under this warranty is limited to reimbursement of the purchase price of the portion of the product proven to be defective. The user assumes all risks and liability resulting from the use of this product.

***Additional product information, technical bulletins and specifications are available online at [www.bomanite.com](http://www.bomanite.com) or through one of our Bomanite Licensed Contractors. For additional assistance with specifications or technical issues, contact The Bomanite Company.***