



Your Single Source For Innovative
Architectural Concrete Solutions

Technical Bulletin and Application Guideline

Page: 1 of 1
June 2009

BOMANITE EXTRA SURE TRAC ANTI-SLIP ADDITIVE FOR HIGH SOLIDS FLOOR COATINGS

PRODUCT DESCRIPTION

Bomanite Extra Sure Trac is a polymeric grit coating additive designed to prevent slippery conditions if the floor seal becomes wet or oily. Bomanite Extra Sure Trac can be easily mixed into both waterborne and solventborne seals, and will not settle out to the bottom. Note: Bomanite Extra Sure Trac in a previously applied coating might contribute to slight foaming in a seal or finish applied over it. Subsequent coats should be applied smoothly with minimal agitation on the floor.

APPLICATION

Bomanite Extra Sure Trac is only recommended for use in high solids coatings. Mix Bomanite Extra Sure Trac into the seal and stir thoroughly. For waterborne and solvent borne coatings, add 200-400 grams Bomanite Extra Sure Trac per gallon of seal. Apply a medium coat of the seal following normal application procedures (application of sealer with Bomanite Extra Sure Trac is restricted to roller, lambswool applicator or mop). Apply the seal as evenly as possible. Frequent mild stirring of the sealer with Bomanite Extra Sure Trac is recommended during application. Bomanite Extra Sure Trac may rise to the surface over time. An additional thin coat of seal without Bomanite Extra Sure Trac may be applied over seal with Bomanite Extra Sure Trac to help trap the grit in the seal and to provide easier cleaning. However, slip resistance may decrease as a result.

SPECIFICATIONS

COLOR	White powder
ODOR	Mild
DOSAGE (recommended)	
For good slip resistance	200 grams per gallon of seal
For extra slip resistance	400 grams per gallon of seal
FLASH POINT	>530 °F (ASTM D-92 COC)
VOLATILE CONTENT	Zero
SPECIFIC GRAVITY	0.90

SPECIFICATION ASSISTANCE

Consult The Bomanite Company for specification assistance, detailing, etc. This consultation is highly recommended prior to specification.

WARRANTY

This product is warranted to meet uniform quality standards within conventional manufacturing tolerances. Since no control is exercised over product use, no warranty or guarantee, expressed or implied, can be made to its use. Seller's and manufacturer's obligation under this warranty is limited to reimbursement of the purchase price of the portion of the product proven to be defective. The user assumes all risks and liability resulting from the use of this product.