



Your Single Source For Innovative  
Architectural Concrete Solutions

## BOMANITE CEMENTITIOUS TOPPING

Cross Reference Guideline

Product Name	Resin Description	Powder Description	VOC Content Liquid	Recommended Uses	Unique Characteristics	Applied Thickness	SF per Coat per Bag	Hazardous Goods
<b>Micro-Top</b>	Proprietary	Portland cement with silica	< 30 grams per liter	<ul style="list-style-type: none"> <li>Interior flooring product</li> <li>Exterior resurfacing with limited freeze-thaw exposure</li> </ul>	<ul style="list-style-type: none"> <li>Interior concrete resurfacer with excellent troweling characteristics and color variety</li> <li>Designed as a wear surface if protected with an appropriate sealer or coating</li> </ul>	1/16" 2 base coats 2 finish coats	450 base coat 600-1000 finish coat	None
<b>Micro-Top XT</b>	Ethylene vinyl acetate	Portland cement with marble	< 5 grams per liter	<ul style="list-style-type: none"> <li>Exterior resurfacing with extended freeze-thaw exposure</li> </ul>	<ul style="list-style-type: none"> <li>Exterior resurfacer with superior flexibility and color variety</li> <li>Designed as a wear surface if protected with an appropriate sealer or coating</li> <li>Softer, more resilient than Micro-Top</li> </ul>	1/8" 2 base coats 2 finish coats	200 base coat 600-800 finish coat	None
<b>Bomanite Thin-Set II</b>	Ethylene vinyl acetate	Portland cement with silica	< 3 grams per liter	<ul style="list-style-type: none"> <li>Interior flooring product</li> <li>Exterior resurfacing with moderate freeze-thaw exposure</li> </ul>	<ul style="list-style-type: none"> <li>Interior or exterior concrete resurfacer with ease of use characteristics and color variety</li> <li>Designed as a wear surface if protected with an appropriate sealer or coating</li> </ul>	1/4" to 3/4" total one lift	22 @ 1/4" 16 @ 3/8" 11 @ 1/2"	None
<b>Bomanite Repair Mortar</b>	Styrene butadiene	Portland cement with silica	< 14 grams per liter	<ul style="list-style-type: none"> <li>Interior below floor patching</li> <li>Exterior below resurfacing patching with moderate freeze-thaw exposure</li> </ul>	<ul style="list-style-type: none"> <li>Interior or exterior patching product for pitching or general repairs</li> <li>Designed to be covered with an appropriate topping, sealer or coating</li> <li>Can be used over wood into 2.5 gauge lathe</li> </ul>	1/4" to 3/4" total one lift 1 1/2" with 20% rock	36 @ 1/4" 27 @ 3/8" 18 @ 1/2"	None

Product Name	Resin Description	Powder Description	VOC Content	Recommended Uses	Unique Characteristics	Applied Thickness	SF per Coat per Bag	Hazardous Goods
<b>Bomanite Repair Mortar FA Fast Set</b>	Carboxylated Styrene Butadiene	Sulfo-aluminate/ Portland cement blend with silica	0 grams per liter	<ul style="list-style-type: none"> <li>Interior below flooring resurfacer</li> <li>Exterior below resurfacing patching with extended freeze-thaw exposure</li> </ul>	<ul style="list-style-type: none"> <li>Interior or exterior fast-setting patching product for improved bond and moisture resistance or general repairs</li> <li>Designed to be covered with an appropriate topping, sealer or coating</li> </ul>	Tight to 1/4" total one lift	200 Tight 36 @ 1/8" 18 @ 1/4"	None
<b>Bomanite Repair Mortar MP Regular Set</b>	Carboxylated Styrene Butadiene	Portland cement with silica	0 grams per liter	<ul style="list-style-type: none"> <li>Interior below flooring resurfacer</li> <li>Exterior below resurfacing patching with extended freeze-thaw exposure</li> </ul>	<ul style="list-style-type: none"> <li>Interior or exterior standard-setting patching product for improved bond or general repairs</li> <li>Designed to be covered with an appropriate topping, sealer or coating</li> </ul>	Tight to 1/4" total one lift	200 Tight 36 @ 1/8" 18 @ 1/4"	None
<b>Bomanite Flexible Repair Mortar</b>	Acrylic	CA3/Portland cement with silica	< 30 grams per liter	<ul style="list-style-type: none"> <li>Interior below flooring resurfacer for large areas or pitching from 1/4"</li> <li>Exterior below resurfacing patching with extended freeze-thaw exposure</li> </ul>	<ul style="list-style-type: none"> <li>Interior or exterior medium-setting patching</li> <li>Designed to be covered with an appropriate topping, sealer or coating</li> <li>Excellent for pitching over wood into 2.5 gauge lathe</li> </ul>	1/4" to 3/4" total one lift	20 @ 1/4" 15 @ 3/8" 10 @ 1/2"	None
<b>Bomanite Self Leveler</b>	Proprietary	Portland cement with silica	N/A	<ul style="list-style-type: none"> <li>Interior flooring product for resurfacing large areas</li> </ul>	<ul style="list-style-type: none"> <li>Interior rapid setting flowable concrete resurfacer</li> <li>Designed as a wear surface if protected with an appropriate sealer or coating</li> <li>For use as a fast patch under Micro-Top</li> </ul>	1/4" to 3/4" total one lift	24 @ 1/4" 18 @ 3/8" 12 @ 1/2"	None
<b>Bomanite SL-Underlayment</b>	Proprietary	Portland cement with silica	N/A	<ul style="list-style-type: none"> <li>Interior flooring product for resurfacing large areas or feather edging isolated areas</li> </ul>	<ul style="list-style-type: none"> <li>Interior rapid-setting flowable concrete resurfacer</li> <li>Designed as a residential wear surface if protected with an appropriate sealer or coating</li> <li>For use as a fast patch under Bomanite Thin-Set II or other 1/4" product</li> </ul>	Tight to 3/4" total one lift	48 @ 1/8" 24 @ 1/4" 12 @ 1/2"	None