

Bomanite Thin-Set II Powder



Material Safety Data Sheet

Bomanite LLC
34501 East Quincy Ave. Building 28
Watkins, CO 80137

HMIS Ratings

Health: 2
Flammability: 0
Reactivity: 1
Personal Protection See VII
Equipment:

Emergency Telephone Number:
Chemtrec: (800) 424-9300

Notice: The following information is accurate to the best of our knowledge and is offered in good faith. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in specific context of the intended use and determine whether they are appropriate.

I. IDENTIFICATION

Product Name: Bomanite Thin-Set II Powder
Synonymous: N/A

Chemical Formula: Proprietary
D.O.T. Hazard Class: Dry building mortar, not regulated.
Appearance & Odor: Gray powder, no odor.

II. HAZARDOUS COMPONENTS & EXPOSURE LIMITS

Composition	%	OSHA TWA	ACGIH TLV	CAS NO.
Portland Cement	<50	10 mg/m ³	10 mg/m ³ Total Dust	65997-15-1
Silica	>50	0.1 mg/m ³	0.1 mg/m ³ Respirable Dust	14808-60-7

III. TYPICAL PHYSICAL & CHEMICAL CHARACTERISTICS

Specific Gravity (H₂O=1): N/A
Boiling Point: N/A
Melting Point: N/A
Vapor Pressure: N/A
Vapor Density: N/A
Evaporation Rate: N/A
Solubility In Water: Slightly Insoluble

IV. FIRE EXPLOSION & REACTIVITY DATA

Flash Point: N/A
Flammable Limits: N/A
Firefighting Media: N/A

Firefighting Procedure: None

Special Firefighting Procedure: N/A

Unusual Fire Hazards: None
Reactivity: Stable
Incompatibilities: None
Decomposition or Byproducts: None
Hazardous Polymerization: Will not occur.
Conditions to Avoid: Keep dry until used.

V. HEALTH HAZARD DATA

Inhalation: May cause irritation to respiratory tract.
Skin Contact: In contact with moisture, can cause irritation or burns.
Eye Contact: In contact with moisture, can cause irritation or burns.
Ingestion: May cause irritation to digestive tract.
Overexposure Effects: Wet cement may cause alkali burns and dry the skin. Free silica dust may cause delayed lung injury. Dust may cause eye and nose inflammation.
Carcinogenic Data: Silica is listed with IARC as a Class 2 carcinogen. Contains silica, which can cause lung damage and cancer. Risk depends upon duration and level of exposure.

Emergency and First Aid Procedures

Inhalation: Move subject to fresh air.
Skin Contact: Wash with soap and water.
Eye Contact: Flush with plenty of water and call a physician.
Ingestion: Call a physician.

VI. SPILL PROCEDURES & WASTE DISPOSAL

Spill: Sweep or vacuum using good ventilation.
Waste Disposal: Dispose of in accordance with Federal, State and Local regulations on solid wastes.
Precautions for Safe Handling And Storage: Store in dry area. After handling, wash hands thoroughly.
Other Precautions: N/A

VII. PROTECTIVE CONTROL MEASURES

Respirator:	If environment is dusty, use NIOSH approved respirator.
Ventilation:	Good local and mechanical exhaust. Follow OSHA standards.
Special:	N/A
Protective Gloves:	Rubber gloves.
Eye Protection:	Tight fitting goggles if area is dusty.
Other Protective Clothing Required:	As needed to protect skin.

Work/Hygiene Practices

Wash hands after use and before eating, drinking or smoking.